



## 650V N-Channel POWER MOSFET

### Features

- $V_{DSS}=650V$     $I_D=10A$
- $R_{DS(ON)}=1.0\Omega(\text{Max.}) @ V_{GS}=10V$
- High Reliability Capability with Passivation
- 100% avalanche tested
- RoHS compliant
- Smart design in high voltage technology.

### PIN DESCRIPTION



### Applications

- LED power supplies
- Cell Phone Charger
- Standby Power

Part Number	Package	Marking	ROHS Status	Packing
SI10N65F	TO-220F	SI10N65F	Pb-Free	Box (Tube)

### Absolute Maximum Ratings ( $T_A=25^\circ\text{C}$ unless otherwise noted)

Symbol	Parameter		Typical	Unit
$V_{DSS}$	Drain-Source Voltage		650	V
$V_{GSS}$	Gate-Source Voltage		$\pm 30$	V
$I_D$	Drain Current		10	A
	$T_C=100^\circ\text{C}$	6	A	
$I_{DM}$	Pulsed Drain Current		34	A
$P_D$	Power Dissipation ( $T_C = 25^\circ\text{C}$ )		55	W
$I_{AR}$	Avalanche Current		3.3	A
$E_{AS}$	Single Pulse Avalanche Energy		345	mJ
$E_{AR}$	Repetitive Avalanche Energy		173	mJ
$T_J, T_{stg}$	Operating Junction and Storage Temperature Range		-55 to 150	°C

### Thermal Resistance

Parameter	Symbol	Value	Unit
Thermal resistance, junction – Case.	$R_{\theta JC}$	2.5	°C/W
Thermal resistance, junction – Ambient.	$R_{\theta JA}$	62.5	

## Electrical Characteristics ( $T_A=25^\circ C$ unless otherwise noted)




Symbol	Parameter	Test Conditions	Min	TYP	Max	Unit
<b>Static Characteristics</b>						
$BV_{DSS}$	Drain-source breakdown voltage	$V_{GS}=0V, I_D=250\mu A$	650	-	-	V
$I_{DSS}$	Zero Gate Voltage Drain Current	$V_{DS}=650V, V_{GS}=0V$	-	-	1	$\mu A$
$I_{GSS}$	Gate-Source Leakage	$V_{GS}=\pm 30V, V_{DS}=0V$	-	-	$\pm 100$	nA
$V_{GS(th)}$	Gate-Source Threshold Voltage	$V_{DS}=V_{GS}, I_D=250\mu A$	2	-	4	V
$R_{DS(on)}$	Drain-Source On-Resistance	$V_{GS}=10V, I_D=5A$	-	-	1.0	$\Omega$
$g_{fs}$	Forward Transconductance	$V_{DS}=40V, I_D=5A$	-	10	-	S
<b>Dynamic Characteristic</b>						
$C_{iss}$	Input Capacitance	$V_{GS}=0V, V_{DS}=25V, f=1MHz$	-	1365	-	pF
$C_{oss}$	Output Capacitance		-	112	-	
$C_{rss}$	Reverse Transfer Capacitance		-	10	-	
$Q_G$	Gate Total Charge	$V_{DS}=520V, I_D=10A, V_{GS}=10V,$	-	26	-	nC
$Q_{gs}$	Gate-Source charge		-	7.4	-	
$Q_{gd}$	Gate-Drain charge		-	11.2	-	
$t_{d(on)}$	Turn-on delay time	$V_{DD}=325V, I_D=10A, R_G=25\Omega, V_{GS}=10V$	-	30	-	nS
$t_r$	Rise time		-	65	-	
$t_{d(off)}$	Turn-off delay time		-	69	-	
$t_f$	Fall time		-	53	-	
<b>Drain-Source Body Diode Characteristics</b>						
$V_{SD}$	Body Diode Forward Voltage	$V_{GS}=0V, I_F=1A$	-	-	1.0	V
$t_{rr}$	Body Diode Reverse Recovery Time	$V_{DS}=100V, I_F=10A, dI_F/dt=100A/\mu s$	-	-	380	nS
$Q_{rr}$	Body Diode Reverse Recovery Charge		-	-	7.2	$\mu C$
$I_S$	Maximum Continuous Drain-Source Diode Forward Current	-	-	10	A	
$I_{SM}$	Maximum Pulsed Drain-Source Diode Forward Current	-	-	34	A	

Note:

1. The value of  $R_{DS(on)}$  is measured with the device in a still air environment with  $T_A = 25^\circ C$ .

2. The static characteristics in Figures 1 to 6 are obtained using  $<300 \mu s$  pulses, duty cycle 2% max

## Switching Time Test Circuit and Waveforms



## ■ Typical Performance Characteristics




Fig 1: On-Region Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current and Gate Voltage




Figure 4: On-Resistance vs. Junction Temperature




Figure 5: Break Down vs. Junction Temperature





Figure 6: Body-Diode Characteristics (Note E)

## Soldering Methods for Products

Profile Feature	Sn-Pb Eutectic Assembly	Pb-Free Assembly
Average ramp-up rate(TL to TP)	<3°C/sec	<3°C/sec
Preheat		
-Temperature Min(Ts min)	100°C	150°C
-Temperature Max(Ts max)	150°C	200°C
-Time(min to max)(ts)	60 to 120 sec	60 to 180 sec
Tsmax to TL		
- ramp-up rate	<3°C/sec	<3°C/sec
Time maintained above:		
-Temperature(TL)	183°C	217°C
-Time(tL)	60 to 150 sec	60 to 150 sec
Peak Temperature(Tp)	240°C+0/-5°C	250°C+0/-5°C
Time within 5 °C of actual Peak Temperature	10 to 30 sec	20 to 40 sec
Ramp-down Rate	<6°C/sec	<6°C/sec
Time 25 °C to Peak Temperature	<6 minutes	<8 minutes

Figure 1: Temperature profile




Note :1.Storage environment: Temperature=10°C to 35@Humidity=45%±15%

- 2.Reflow soldering of surface-mount devices
- 3.Flow(wave) soldering(solder dipping)

Products	Peak Temperature	Dipping Time
Pb devices	245°C±5°C	5sec±1sec
Pb-free devices	250°C+0/-5°C	5sec±1sec

## Package Outline



Millimeter(mm)					
Symbol	Min	Max	Symbol	Min	Max
A	4.50	4.90	E	9.96	10.36
A1	2.44	2.64	E1	8.00TYP	
A2	0.60	0.80	e	2.54TYP	
A3	2.56	2.96	e1	5.08TYP	
b	0.70	0.95	H	6.50	6.90
b1	1.28TYP		L	12.48	13.20
c	0.45	0.65	L1	2.93TYP	
D	15.67	16.07	P1	2.98	3.38
D1	7.70TYP		P2	3.20.	3.60

## Important Notice

Si-Trend reserves the right to change all product、product specifications and data without prior notice ; Our customer Please confirm to place an order confirmation before make the integrity of information complete and up-to-date。

Any semiconductor under specific conditions are possible to certain failure or malfunction rate ; Customers are responsible in the use of Si-Trend products to system design and manufacturing in compliance with safety standards and adopting safety measures, To avoid the potential risk of failure may cause the personal safety and property loss.

Si-Trend Always refine on to provide more excellent products

## Modify record

Date	Version	Description	Pagination
20170825	A.0	original	7